VBG GROUP

SAFETY DATA SHEET

38-235405h

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	MEK OLJA
Registration number	-
Synonyms	None.
Product code	BDS001136AE
Issue date	24-May-2022
Version number	2.0
Revision date	17-February-2023
Supersedes date	24-May-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Lubricants
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company: **VBG GROUP TRUCK EQUIPMENT AB**
Box 1216
SE-462 28 VÄNERSBORG
Tel: +46 (0) 521-27 77 00 (Office time)
www.vbg.eu
chemical.vbgte@vbggroup.com

In case of emergency: **+ 44 1925 23 41 11 (Office time)**

Sales company		Tel
VBG GROUP SALES A/S, DENMARK	Industribuen 20-22, 5592 Ejby	+45 64 46 19 19
VBG GROUP SALES AS, NORWAY	Karihaugveien 102, 1086 Oslo	+46 23 14 16 60
VBG GROUP SALES LIMITED, GREAT BRITAIN	Unit 7, Gemini8 Business Park Apollo Park, Charon Way Warrington , WA5 7AE	+44 1925 23 41 11
VBG GROUP TRUCK EQUIPMENT GMBH, GERMANY	Girmesgath 5, 47803 Krefeld	+49 (0)2151-835-0
BG GROUP TRUCK EQUIPMENT NV, BELGIUM	Industrie Zuid Zone 2.2 Lochtemanweg 50, 3580 Beringen	+32 11 458 379
VBG GROUP TRUCK EQUIPMENT NV, NETHERLANDS	Alaertslaan 12, 5801 DC Venray	+31 478 514 143

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
Health hazards		
Skin sensitisation	Category 1B	H317 - May cause an allergic skin reaction.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Benzenesulfonic acid, mono-C16-24-alkyl derivitives, calcium salts, Polysulfides, di-tert-dodecyl

Hazard pictograms

Signal word Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H317	May cause an allergic skin reaction.

Precautionary statements

Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P280	Wear protective gloves.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - 25	- 926-141-6	01-2119456620-43	-	
Classification: Asp. Tox. 1;H304					
Distillates, petroleum, hydrotreated light paraffinic	5 - 15	64742-55-8 265-158-7	01-2119487077-29	649-468-00-3	
Classification: Asp. Tox. 1;H304					L
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified [complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers pr	1 - 5	64742-54-7 265-157-1	01-2119484627-25	649-467-00-8	
Classification: Asp. Tox. 1;H304					

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts	<1	68584-23-6 271-529-4	01-2119492627-25	-
Classification: Skin Sens. 1B;H317				
Calcium petroleum sulfonate	<1	61789-86-4 263-093-9	01-2119488992-18	-
Classification: Skin Sens. 1;H317				
Polysulfides, di-tert-dodecyl	<1	68425-15-0 270-335-7	01-2119540516-41	-
Classification: Skin Sens. 1B;H317				
Benzenesulfonic acid, mono-C16-24-alkyl derivitives, calcium salts	<0.25	70024-69-0 274-263-7	01-2119492616-28	-
Classification: Skin Sens. 1;H317				
2,2'-(octadec-9-enylimino)bisethanol	<0.1	25307-17-9 246-807-3	01-2119510876-35	-
Classification: Acute Tox. 4;H302, Skin Corr. 1;H314, Eye Dam. 1;H318, Aquatic Acute 1;H400(M=10), Aquatic Chronic 1;H410				

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.
M: M-factor
vPvB: very persistent and very bioaccumulative substance.
PBT: persistent, bioaccumulative and toxic substance.
#: This substance has been assigned Union workplace exposure limit(s).
Note L - The harmonized classification as a carcinogen does not apply because the substance contains less than 3 % DMSO extractable material as measured by IP 346.
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO_2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
7.3. Specific end use(s)	Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General population

Components	Value	Assessment factor	Notes
2,2'-(octadec-9-enylimino)bisethanol (CAS 25307-17-9)			
Long-term, Systemic, Dermal	0.214 mg/kg	140	developmental toxicity / teratogenicity
Long-term, Systemic, Inhalation	0.745 mg/m3	35	developmental toxicity / teratogenicity
Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts (CAS 68584-23-6)			
Long-term, Local, Dermal	0.513 mg/cm2	10	Skin Sensitisation
Long-term, Systemic, Inhalation	2.9 mg/m3	150	Repeated dose toxicity
Calcium petroleum sulfonate (CAS 61789-86-4)			
Long-term, Local, Dermal	0.513 mg/cm2	10	Skin Sensitisation
Long-term, Systemic, Inhalation	2.9 mg/m3	150	Repeated dose toxicity
Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)			
Long-term, Local, Inhalation	1.19 mg/m3	75	Repeated dose toxicity
Long-term, Systemic, Oral	0.74 mg/kg	120	Repeated dose toxicity
Polysulfides, di-tert-dodecyl (CAS 68425-15-0)			
Long-term, Systemic, Dermal	16.7 mg/kg	600	Repeated dose toxicity
Long-term, Systemic, Inhalation	5.8 mg/m3	150	Repeated dose toxicity
Long-term, Systemic, Oral	1.7 mg/kg	600	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
2,2'-(octadec-9-enylimino)bisethanol (CAS 25307-17-9)			
Long-term, Systemic, Dermal	0.3 mg/kg	100	developmental toxicity / teratogenicity
Long-term, Systemic, Inhalation	2.112 mg/m3	25	developmental toxicity / teratogenicity
Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts (CAS 68584-23-6)			
Long-term, Local, Dermal	1.03 mg/cm2	5	Skin Sensitisation
Long-term, Systemic, Inhalation	11.75 mg/m3	75	Repeated dose toxicity
Calcium petroleum sulfonate (CAS 61789-86-4)			
Long-term, Local, Dermal	1.03 mg/cm2	5	Skin Sensitisation
Long-term, Systemic, Inhalation	11.75 mg/m3	75	Repeated dose toxicity
Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)			
Long-term, Local, Inhalation	5.58 mg/m3	45	Repeated dose toxicity
Long-term, Systemic, Dermal	0.97 mg/kg	72	Repeated dose toxicity
Polysulfides, di-tert-dodecyl (CAS 68425-15-0)			
Long-term, Systemic, Dermal	46.7 mg/kg	300	Repeated dose toxicity
Long-term, Systemic, Inhalation	32.9 mg/m3	75	Repeated dose toxicity

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
2,2'-(octadec-9-enylimino)bisethanol (CAS 25307-17-9)			
Freshwater	0.214 µg/l	50	
Secondary poisoning	2 mg/kg	300	Oral
Sediment (freshwater)	1.692 mg/kg	50	
Soil	5 mg/kg	100	
Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)			
Secondary poisoning	9.33 mg/kg		Oral
Polysulfides, di-tert-dodecyl (CAS 68425-15-0)			
Secondary poisoning	66.7 mg/kg	300	Oral
Sediment (freshwater)	3.85 mg/kg	100	
Sediment (marine water)	0.385 mg/kg	1000	
STP	1 g/l	10	

8.2. Exposure controls

Appropriate engineering controls: Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection: Use eye protection conforming to EN 166. Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection: When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

- Other: Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge. (Filter type A)

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

Hygiene measures: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid.

Form: Aerosol.

Colour: Not available.

Odour: Not available.

Odour threshold: Not available.

pH: Not available.

Melting point/freezing point: 0 °C (32 °F) estimated

Initial boiling point and boiling range: Not available.

Flash point: 75.0 °C (167.0 °F) Closed cup

Evaporation rate: Not available.

Flammability (solid, gas): Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%): Not available.

Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.82 at 20°C
Solubility(ies)	
Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
Viscosity	6.5 - 7 mPa·s at 20°C 4.38 mPa·s at 40°C
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

Aerosol spray enclosed space	
Deflagration density	Not available.
Aerosol spray ignition distance	Not available.
VOC	325 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Based on available data, the classification criteria are not met.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.

Components	Species	Test Results
2,2'-(octadec-9-enylimino)bisethanol (CAS 25307-17-9)		
Acute		
Oral		
LD50	Rat	1260 mg/kg
Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts (CAS 68584-23-6)		
Acute		
Oral		
LD50	Rat	> 20000 mg/kg
Calcium petroleum sulfonate (CAS 61789-86-4)		
Acute		
Dermal		
LD50	Rat	> 4000 mg/kg

Components	Species	Test Results
Oral		
LD50	Rat	> 16000 mg/kg

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified [complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers pr (CAS 64742-54-7)

Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	> 5 mg/l/4h
Oral		
LD50	Rat	> 5000 mg/kg

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	> 5000 mg/m3, 8 h
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory sensitisation	Based on available data, the classification criteria are not met.
Skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified [complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers pr (CAS 64742-54-7)	3 Not classifiable as to carcinogenicity to humans.
Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)	3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Not likely, due to the form of the product.
Mixture versus substance information	Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
2,2'-(octadec-9-enylimino)bisethanol (CAS 25307-17-9)			
Aquatic			
Acute			
Algae	EC50	Algae	0.0538 mg/l, 72 hours
Crustacea	EC50	Daphnia	0.043 mg/l, 48 hours
Fish	LC50	Fish	0.1 mg/l, 96 hours

Components		Species	Test Results
Chronic			
Crustacea	NOEC	Daphnia	0.6 - 2.1 mg/l, 21 days
Calcium petroleum sulfonate (CAS 61789-86-4)			
Aquatic			
Acute			
Fish	LC50	Fish	> 10000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified [complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers pr (CAS 64742-54-7)			
Aquatic			
Acute			
Algae	EC50	Algae	> 100 mg/l, 48 hours
Crustacea	EC50	Daphnia	> 10000 mg/l, 48 hours
Chronic			
Crustacea	NOEL	Daphnia	10 mg/l, 21 days
Fish	NOEL	Fish	> 1000 mg/l, 21 days
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
Aquatic			
Acute			
Crustacea	EC50	Daphnia	1000 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss	1000 mg/l, 96 h

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow) Not available.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.
GWP: 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS, flammable

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Hazard No. (ADR) Not assigned.

Tunnel restriction code	D
ADR/RID - Classification code:	5F
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

ADN; ADR; IATA; IMDG; RID

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified [complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers pr (CAS 64742-54-7)
Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
CAS: Chemical Abstract Service.
Ceiling: Short Term Exposure Limit Ceiling value.
CEN: European Committee for Standardization.

	CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures. GWP: Global Warming Potential. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. MAC: Maximum Allowed Concentration. MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG). MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic. REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. VOC: Volatile organic compounds. vPvB: Very persistent and very bioaccumulative. STEL: Short-term Exposure Limit.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full under sections 2 to 15	H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H410 Very toxic to aquatic life with long lasting effects.
Revision information	Composition / Information on Ingredients: Disclosure Overrides
Training information	Follow training instructions when handling this material.
Disclaimer	CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.